



WA480-6A LOADER



This Dash 6 machine offers outstanding durability with powerful hydraulics from variable displacement piston pumps, combined with a closed-centre Load sensing system. The torque convertor driveline delivers excellent rim pull to penetrate the densest materials to ensure high productivity.

BUCKET CAPACITY

3.8-6.1m³³

POWER UNIT

Drive	4 Cycle, turbo charged
Type	Komatsu SAA6D125E-5
Power	223kW/2000rpm
Cooling	Water cooled
Fuel Tank	413 Litres

HYDRAULICS STEERING SYSTEM

Double acting, piston type hydraulic cylinders	
Capacity	195l/min

HYDRAULICS LOADER CONTROL

Double acting, piston type hydraulic cylinders	
Capacity	242l/min

TRANSPORT DIMENSIONS

Length	3450mm
Width	3010mm
Height	3500mm
Weight	34400kg (approximately)

STANDARD EQUIPMENT

2 Spool vale for boom and bucket controls; alternator; 50A auto shift transmission with mode select system; back up alarm; back up lamp; batteries; 12Vx2; counterweight; directional signal; engine shut-off system; electric; hard water area arrangement (corrosion register); hydraulic-driven fan with reverse rotation; lift cylinders and bucket cylinder; main monitor panel with EMMS; PPC fingertip control; two levers; radiator mask; lattice type; rear view mirror for cab; rear window washer and wiper; ROPS/FOPS cab; seat belt; seat; suspension type with reclining; service brakes; wet disc type; starting motor; 7.5kW; steering wheel; tiltable; telescopic; sun visor; tires and rims; transmission; 4 forward and 4 reverse.