



TESAB 1210 IMPACTOR

NOTE: INFORMATION AND PHOTOGRAPHS ARE FOR BASE UNITS AND MAY NOT BE SPECIFIC TO UNITS OFFERED



The TESAB 1210 tracked impact crusher is designed to accept a large feed size and produce consistent, high quality end product at a low cost per ton. Suitable for both primary and secondary applications the TESAB 1210 can work standalone or integrate easily into existing crushing and screening operations.

CRUSHER

Heavy Duty Horizontal Shaft Rotor w/Speed Sensor	
Feed Opening	1020mm x 780mm
Max Feed Size	500mm (Depending on Material Density)
Setting	15mm – 100mm (Min-Max)
Drive	Direct Drive V-Belt (8 off)
Adjustment	Hydraulic (Middle Apron & Bar Carrier)

FEEDING

Start/Stop Remote Control Function	
Hopper	9.2m ³ Capacity
Hyd. Folding w/Locking Wedge System=Decreased Setup Time	
Length / Width	4800mm / 2800mm
Heavy Duty	15mm Hopperwall Plates
Primary Feeder	HD Plate Feeder - Spring Mounted
Vibrating Twin Shaft Geared Design w/Hardox Base Plate	
Length	2600mm
Width	900mm
Variable Speed	0-950rpm
Scalping Pre-screen	Independent Double Deck
Variable Speed, Direct Drive with Flexible Coupling	
Top Deck Dim.	1750mm x 1000mm
Bottom Deck Dim.	950mm x 1000mm

POWER UNIT

Drive	Diesel/Hydraulic
Type	CAT C13
Power	328kW / 440HP
Engine Speed	1800rpm
Fuel/Hyd. Tank Cap.	800L / 850L

CONVEYORS

Main Product Width	1000mm
Discharge Height	3540mm
Belt Speed	110m/min
Hydraulically Folding Product Conveyor	
Side Dirt Width	650mm
Discharge Height	2990mm
Belt Speed	100m/min
Hydraulically Folding Telescopic Dirt Conveyor	
Recirculating/Return	Fitted

SAFETY FEATURES

- Engine Safety Shutdown Systems
- Full Safety Guarding for Nip Points
- Crusher Speed Protection Systems
- Key Switch Operated Tracking System
- 10 Second Start and Tracking Delays
- Easy Access Lubrication Points

DIMENSIONS

	Transport	Working
Length	14250mm	15700mm
Width	3330mm	2900mm
Height	3810mm	
Weight (approx.)	45200kg	

